

2018

Hot-Farm 466 9500# & 9500# Tractor 2 hooks only

1. Motor and Turbo Charger Limitations:
 - a. Fuel pump-P-pump
 - b. One turbo charger per tractor-specifications: 3" inlet and 3" outlet
MAXIMUM; No sleeves, no slots. Maximums will be measured at the wheel face. (Inlet and Outlet)-air wheels must protrude into the inlet and outlet openings. Small base.
 - c. Diesel Fuel ONLY
2. OME Stock INTAKE and Stock EXHAUST Manifolds ONLY.
3. Water:
 - a. Water Injection ONLY
 - b. NO ALCOHOL (i.e., Methanol, Ethanol and etc.) Water injection PUMP lubrication oil is ACCEPTABLE
4. Motor Appearance:
 - a. Stock engine Block, No Deck Plate(s), Stock Heads –No steel Billet or Aluminum heads.
 - b. No Inner coolers allowed.
 - c. Maximum 466 cubic inch limit.
5. Transmission:
 - a. Factory transmission. **Can run** bolt-in transmissions, Gear changes inside Transmission are acceptable.
6. Tire size:
 - a. 20.8 x 38 maximum, **double cut tires allowed, radial or bias ply. Tire circumference not to exceed 220"**.
7. Roll cages are required.
8. Evaluate weights after 3 pulls.
9. Wheelie bars, frame tie bars, side shields, 3/8 inch bolt cross in exhaust pipe, seat belts, and dead men throttle.
10. General rules also apply.
11. Protest rule will follow NTPA rule book. Protestor must put up \$500.00. Tech person receives \$200.00 and owner receives \$300.00 if found legal. If found illegal \$300.00 goes to protester.