

## **11,000# Open 2.4 Altered Farm**

OEM Motor and Block. Block is not to be altered in any way externally for mounting of fuel injection pumps and remain in stock location. Internal webbing and water jacket to remain intact with provisions to re-bore block. OEM Transmission must be stock appearing. No aftermarket gear boxes. Clutch housing, transmission case, rear end housing must be OEM or equivalent. Custom Frames and tube chassis are allowed. Must meet Tech and Class rep approval.

Must have OEM cylinder head, intake manifold and exhaust manifold for that model or series tractor. No filler heads, single feed intake manifolds only. No headers or custom intakes manifolds.

1 inch intake manifold spacer allowed.

505 Cubic inch limit. Under 470 may alter the bore and stroke of the engine to a max of 470 cubic inch.

Exceptions: Massey Ferguson 540, Cockshutt, Oliver and White 585. They must retain factory bore and stroke.

P-Pump: P7100 Max

Wheelbase is a maximum of 114 inches unless produced by manufacture. Maximum of 13 feet from the center of the rear axle to the forward most part.

Full Sheet metal to be in stock location and appearance. Including Hood and grill.

Must have a wide front end. Will be subject to inspection.

Max of 2.4" S300SX-E turbo allowed

No injectables allowed.

Water injection is allowed: Max of 2 ports in crossover pipe.

Crossover pipe to be no more than 3.25" diameter

Turbo must be sealed by FVP

3000 RPM max

No intercoolers or cooling devices allowed

Pullers are required to wear full fireproof Jacket, Pants and Helmet